

# BLAZER Pro Series

## 1000VA & 2000VA



### Ideal for protecting:

- PC, workstations
- POS, ATM, KIOSKS
- NAS, Network equipment
- Critical electronic devices

### KEY FEATURE

- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR to stabilize output voltage
- Wide input voltage & frequency range, comply with generator
- Surge protection for both power line and data line (phone/modem)
- Built-in DC start function enables UPS to be started up without AC power supplied
- Super-fast charger shortens the charging time to 2-4 hours
- Auto charging even though the UPS is off
- Auto restart while mains recovery
- USB HID Smart Battery interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS and Linux
- Full protection against over-discharge, overcharge, overload
- Sealed lead-acid, maintenance free battery

### SPECIFICATION

INPUT	Nominal Voltage	220VAC, 50/60Hz
	Voltage Range	162 - 268 VAC
	Connection	IEC320-10A inlet
OUTPUT	Voltage Regulation	220VAC +/- 10% (Battery mode)
	Frequency Regulation	50Hz or 60Hz +/- 1Hz (Battery mode)
	Receptacles	IEC320-10A outlet
DATA LINE SURGE PROTECTION		RJ45(1000/2000VA)
COMMUNICATIONS		USB port, HID power device
OPERATING ENVIRONMENT		Temperature: 0-40°C Relative Humidity: 0-90% (non-condensing)
SAFETY		CE
WARRANTY		2 Years: Parts, Service & Battery (Carry-in)

Model	Power Rating	Back-up Time*	Net Weight (kg)	Output Receptacles	Dimensions (W x D x H) mm
BLAZER 1000 Pro	1000VA/600W	18 min (2 PCs load)	8.8	6	139 x 365 x 195
BLAZER 2000 Pro	2000VA/1200W	25 min (2 PCs load)	10.3		

- \* All internal batteries are default as STK brand, any other battery brand might be applied without prior notice.
- \* It's approximate and may vary with equipment, configuration, battery age, temperature, etc.
- \* In the interests of continuous product improvement, all specifications are subject to change without notice.

