

ROBUST Series

650 / 1200VA

Ideal for protecting:

- PC, workstations
- POS, ATM, KIOSKS
- NAS, Network equipment
- Critical electronic devices



KEY FEATURE

- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR to stabilize output voltage
- Wide input voltage & frequency range, comply with generator
- Built-in DC start function enables UPS to be started up without AC power supplied
- Auto charging even though the UPS is off
- Auto restart while mains recovery
- Full protection against over-discharge, overcharge, overload
- Sealed lead-acid, maintenance free battery

SPECIFICATION

MODEL		R650	R1200
POWER RATING	VA/W	650VA/360W	1200VA/600W
INPUT	Voltage	230VAC	
	Voltage Range	140-300VAC	
	Frequency	>40Hz (comply with generator)	
OUTPUT	Voltage	230VAC	
	Voltage Regulation (Batt. Mode)	+/-10%	
	Frequency	50Hz/60Hz	
	Frequency Regulation (Batt. Mode)	+/-1 Hz	
BACKUP TIME*	Receptacles	Universal x 2	Universal x 4
	1PC load	15 minutes	30 minutes
PHYSICAL	Dimension, WxDxH	100 x 278 x 143 mm	139 x 365 x 195 mm
	Net Weight	4.4kg	9.2kg
ENVIRONMENT	Operating Environment	Temperature: 0-40 °C Relative Humidity: 0-90% (non-condensing)	
	Noise Level	Less than 40dB	
WARRANTY		2 Years: Parts, Service & Battery (Carry-in)	



To inquire, please call or email:

+63 2 858 5555 / +63 2 625 5900 • sales@wsiphil.com.ph

Metro Manila WSI Corporate Center, 1005 Metropolitan Avenue, Makati City, Philippines 1205 • Fax +63 2 858 5511 • Email sales@wsiphil.com.ph
 Cebu 38 V. Sotto Street, Brgy. Tinago, Cebu City • Tel +63 32 255.1012 to 14 • Fax +63 32 255 1011 • Email sales@wsiphil.com.ph
 Davao Unit 11 Plug Holdings Bldg. 141 R. Castillo Street Agdao, Davao City 8000 • Tel +63 82 284 0098 • Fax +63 82 300.7463 • Email sales@wsiphil.com.ph

