



# PHOENIX ULTIMA SERIES

## Line-Interactive UPS



### Key Features

- ▶ Automatic Voltage Regulation (AVR)
- ▶ Auto-Restart/Auto-charge
- ▶ Cold Start Function
- ▶ Off-mode Charging
- ▶ Compact Size

Model	UA650	UA850
Capacity	650VA/360W	850VA/480W
<b>Input</b>		
Voltage	220-240V	
Voltage Range	140-300Vac	
Frequency	50/60Hz (Auto-sensing)	
<b>Output</b>		
Voltage (Battery)	220-240V	
Frequency (Battery)	50/60Hz±1%	
Waveform (Battery)	Simulated Sine Wave	
Transfer Time	4ms Typical	
Outlet Type	4 NEMA 5-15R	2 Universal Sockets
Protection	Overload, Short Circuit, Over Discharge and Over Charge	
<b>Battery</b>		
Typical Back-up Time	5-15 minutes	5-20 minutes
Sealed Lead-acid Battery	12V 5AH * 1	
Typical Recharge Time	6 hours	8 hours max (recharge time to 90% of capability)
<b>Indicators</b>		
Display	LED default	
Alarm	Battery Mode, Low Battery, Overload, Fault, etc.	
<b>Management</b>		
Auto Recharge	Yes	
Auto Restart	Yes	
<b>Physical</b>		
Dimensions (WxHxD) (mm)	84 x 159 x 252	84 x 158 x 252
Netweight (kg)	3.8	4.2
<b>Environment</b>		
Temperature and Humidity	0° to +40°C, 0 to 90% Relative Humidity (Non-condensing)	
Noise Level	Less than 40dB	



Value-Added Distributor



To inquire, please call or email:

+63 2 858 5555 / +63 2 625 5900 • sales@wsiphil.com.ph

Metro Manila WSI Corporate Center, 1005 Metropolitan Avenue, Makati City, Philippines 1205 • Fax +63 2 858 5511 • Email sales@wsiphil.com.ph  
 Cebu 38 V. Sotto Street, Brgy. Tinago, Cebu City • Tel +63 32 255,1012 to 14 • Fax +63 32 255 1011 • Email sales@wsiphil.com.ph  
 Davao Unit 11 Plug Holdings Bldg, 141 R. Castillo Street Agdao, Davao City 8000 • Tel +63 82 284 0098 • Fax +63 82 300.7463 • Email sales@wsiphil.com.ph

