

PHOENIX VALIANT 650

Line-Interactive UPS

Key Features

- Automatic Voltage Regulation (AVR)
- Auto-restart/ Auto-charge
- LCD Panel
- Generator Compatible
- Cold Start Function
- Off-line Charging
- USB



MODEL	PHOENIX VALIANT 650
Capacity	650VA/360W
Input	
Voltage	220-240V
Voltage Range	160-290Vac
Frequency	50/60Hz (Auto Sensing)
Output	
Voltage (Battery)	220-240V
Frequency (Battery)	50/60Hz±1%
Waveform (Battery)	Simulated Sine Wave
Transfer Time	4ms Typical
Outlet Type	3 Universal Sockets
Protection	Overload, Short Circuit, Over discharge and Over charge.
Battery	
Typical Back-up Time	5-20 minutes
Sealed Lead-acid Battery	12V 7AH * 1
Typical Recharge Time	8hours max (recharge time to 90% of capability)
Indicators	
Display	LCD Panel
Alarm	Battery Mode. Low Battery, Overload. Fault. etc.
Interface	
	USB
Management	
Auto Recharge	Yes
Auto Restart	Yes
Power Management Software	Yes
Physical	
Dimensions (W x H x D)(mm)	96 x 138 x 286
Net Weight (kg)	4.3
Environment	
Temperature and Humidity	0°C to +40°C, 0 to 90% Relative
	Humidity (Non-condensing)
Noise Level	Less than 40dB

Exclusively Distributed By: