

# PHOENIX UA650-II

Line-Interactive UPS



### Key Features:



Automatic  
Voltage  
Regulation



Compact  
Size



Auto Start /  
Auto Charge



Cold Start  
Function



Off-node  
Charging

### Technical Specifications

Model	Phoenix UA650-II
Capacity	650VA / 360W
<b>Input</b>	
Voltage Range	140~300Vac
Frequency Range	50/60Hz (Auto Sensing)
<b>Output</b>	
Output voltage	220-240VAC
Frequency Range (batt.mode)	50/60Hz +/- 1%
Wave form (batt.mode)	Simulated Sine Wave
Protection	Overload, Short Circuit, Over Discharge and Over charge
Outlet Type	NEMA*6
<b>Battery</b>	
Back-up time	5-15 minutes
Sealed Maintenance Free Load Acid Battery	12V 7AH
Typical Recharge Time	8hours max (recharge time to 90% of capability)
<b>Indicators</b>	
Display	LED default
Audible Alarm	Battery Mode. Low Battery, Overload. Fault. etc.
<b>Environmental</b>	
Operating Temperature	0°C to +40°C
Operating Relative Humidity	0 to 90% Relative
<b>Management</b>	
Auto Recharge	Yes
Auto Restart	Yes
<b>Physical</b>	
Dimension (W * H * D)(mm)	96*138*286
Net Weight (kgs)	4.0